

CD-50-D-1 and CD-100-D-1 Carbon Dioxide Wheeled Extinguishers

Features

- Simple operation and maintenance
- Portable, compact design
- Non-corrosive, non-conductive, clean extinguishing agent
- Available in 50 lb (23 kg) and 100 lb (45 kg) models
- UL or ULC listed models available
- One person operation
- Large 16 in. (41 cm) semi-pneumatic rubber wheels
- Upright positive on-off operation utilizing the squeeze grip activation, precision machined, chrome plated, forged valves
- DOT/TC approved steel cylinder mounted to a wheeled carriage for ease of mobility
- CD-50-D-1 unit is equipped with 15 ft (4.6 m) and CD-100-D-1 unit is equipped with 40 ft (12.2 m) of rubber-jacketed, wire-braided, high-pressure discharge hose
- Suitable for use in temperatures from -22 °F to 120 °F (-30 °C to 49 °C)



433537/433539

Application

ANSUL Carbon Dioxide Wheeled Fire Extinguishers are designed to protect areas where Class B (flammable liquids and gases) or Class C (energized electrical equipment) fires could occur. They may be used where winds and drafts do not affect discharge or where a clean extinguishing agent is required.

Typical applications include:

- Aviation hangers
- Paint spray booths
- Quench tanks
- Metal tube manufacturing

Model	CD-50-D-1	CD-100-D-1
Part No.	433537 (UL) 433539 (ULC) 435823 (Arabic)	433538 (UL) 433540 (ULC) 435824 (Arabic)
Capacity	50 lb (22.7 kg)	100 lb (45.4 kg)
UL/ULC Rating	20-B:C	20-B:C
Discharge Time	35 seconds	70 seconds
Effective Range	10-12 ft (3.1-3.7 m)	10-12 ft (3.1-3.7 m)
Weight	255 lb (106.6 kg)	400 lb (181.4 kg)
Height	58 3/4 in. (1500 mm)	57 in. (1450 mm)
Width	20 in. (508 mm)	29 in. (737 mm)
Depth	28 in. (710 mm)	28 in. (710 mm)

C.F.H. SÉCURITÉ INC.

1455 Boul. Pitfield • Ville St-Laurent, P.Q. H4S 1G3 • (514) 333-3389 • Fax : (514) 333-1887 • www.cfhsecurite.com